UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/577,288	01/15/2007	Michael Goessel	1431.135.101/FIN516PCT/US	2861

25281   7590   06/16/2010

DICKE, BILLIG & CZAJA
FIFTH STREET TOWERS
100 SOUTH FIFTH STREET, SUITE 2250
MINNEAPOLIS, MN 55402

EXAMINER
MCMAHON, DANIEL F

ART UNIT	PAPER NUMBER
2117	

MAIL DATE	DELIVERY MODE
06/16/2010	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)
Office Action Summary	10/577,288	GOESSEL ET AL.
	Examiner	Art Unit	
	DANIEL F. MCMAHON	2117	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE <u>3</u> MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

1) ☒ Responsive to communication(s) filed on <u>05 April 2010</u>.

2a) ☐ This action is **FINAL**.   2b) ☒ This action is non-final.

3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

4) ☒ Claim(s) <u>35-53 and 55-58</u> is/are pending in the application.

　　4a) Of the above claim(s) _____ is/are withdrawn from consideration.

5) ☒ Claim(s) <u>53</u> is/are allowed.

6) ☒ Claim(s) <u>35-52 and 55-58</u> is/are rejected.

7) ☐ Claim(s) _____ is/are objected to.

8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

9) ☐ The specification is objected to by the Examiner.

10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.

　　Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).

　　Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

　　a) ☒ All　b) ☐ Some * c) ☐ None of:

　　　1. ☒ Certified copies of the priority documents have been received.

　　　2. ☐ Certified copies of the priority documents have been received in Application No. _____.

　　　3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

　　* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1) ☒ Notice of References Cited (PTO-892)

2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)

3) ☒ Information Disclosure Statement(s) (PTO/SB/08)
　　Paper No(s)/Mail Date <u>04292010</u>.

4) ☐ Interview Summary (PTO-413)
　　Paper No(s)/Mail Date. _____ .

5) ☐ Notice of Informal Patent Application

6) ☐ Other: _____ .

DETAILED ACTION

Continued Examination Under 37 CFR 1.114

1.   A request for continued examination under 37 CFR 1.114, including the fee set

forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this

application is eligible for continued examination under 37 CFR 1.114, and the fee set

forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action

has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on March

4, 2010 has been entered.

This action is in response to the amendment filed March 4, 2010.

Claim 53 is allowed.

Claim 35 has been amended.

Claims 35 – 53 and 55 – 58 are pending in the application.

Response to Arguments

2.   Applicant's arguments, regarding Hasegawa, filed March 4, 2010, with respect to

the rejection of claim 35 under 35 U.S.C. 103, regarding the amended claim language

"where z represents state vectors and A and B represent the state matrices of the linear

automation circuits, where the state matrices A and B can be inverted, and where a

dimension L of state vectors z is $\geq$ k, where in A $\neq$ B" has been fully considered but are

moot in view of the new ground(s) of rejection.

Claim Rejections - 35 USC § 103 (New)

3.   The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all

obviousness rejections set forth in this Office action:

> (a) A patent may not be obtained though the invention is not identically disclosed or described as set
> forth in section 102 of this title, if the differences between the subject matter sought to be patented and
> the prior art are such that the subject matter as a whole would have been obvious at the time the
> invention was made to a person having ordinary skill in the art to which said subject matter pertains.
> Patentability shall not be negatived by the manner in which the invention was made.

4.   Claims 35, 51, 52, and 55 are rejected under 35 U.S.C. 103(a) as being

unpatentable over Hasegawa et al. U.S. Publication 2004/0246337 (herein Hasegawa),

in view of Wu, U.S. Patent 5,831,992 (herein Wu).

5.   Regarding claim 35, Hasegawa teaches: an evaluation circuit for detecting and/or

locating faulty data words in a data stream Tn (abstract) comprising: a first linear

automaton circuit and a second linear automaton circuit connected in parallel (figure 4,

element 2, element 16), each having a set of states, wherein the first linear automaton

circuit and the second linear automaton circuit each have inputs that are commonly

connected (figure 4, connections to element 16; figure 5, connection to element 2) for

receiving a data stream Tn comprising n successive data words $y(1), ..., y(n)$ each

having a width of k bits, $k > 1$, (figure 4); a first logic combination gates arranged

downstream of the first linear automaton circuit and also a second logic combination

gates arranged downstream of the second linear automaton circuit, (figure 4, element 4,

element 6); the logic combination gates are designed such that the signature

respectively calculated by the linear automaton circuit can be compared with a

predeterminable good signature and a comparison value can be output (paragraph 65,

lines 35 – 38; paragraph 66, lines 32 – 35); and the first linear automaton circuit and the

second linear automaton circuit are designed such that a first signature and a second

signature, respectively, can be calculated of each data word (paragraph 0066, page 5,

lines 15 – 17).

Hasegawa does not explicitly teach: the first linear automaton circuit can be

described by the following equation z(t + 1) = Az(t) XOR y(t); the second linear

automaton circuit can be described by the following equation z(t+ 1) = Bz(t) XOR y(t);

and where z represents state vectors and A and B represent the state matrices of the

linear automaton circuits, where the state matrices A and B can be inverted, and where

the dimension L of the state vectors is ≥ k, wherein A ≠ B.

Wu teaches: the first linear automaton circuit can be described by the following

equation z(t + 1) = Az(t) XOR y(t) (figure 3, element 14); the second linear automaton

circuit can be described by the following equation z(t+ 1) = Bz(t) XOR y(t) (figure 3,

element 24); and where z represents state vectors and A and B represent the state

matrices of the linear automaton circuits, where the state matrices A and B can be

inverted, and where the dimension L of the state vectors is ≥ k (column 4, lines 55 – 64;

column 5, lines 3 – 17), wherein A ≠ B (column 8, lines 47 – 58 (note: examiner believes

lines 53 should read 14, 24)).

A person of ordinary skill in the art, at the time of the invention, would find it

obvious to combine the teachings of Hasegawa: a first linear automaton circuit and a

second linear automaton circuit connected in parallel, and a first logic combination gates

arranged downstream of the first linear automaton circuit and a second logic

combination gates arranged downstream of the second linear automaton circuit, with

the teaching of Wu: a linear automaton circuit can be described by the following

equation $z(t + 1) = Az(t)$ XOR $y(t)$ and A can be inverted, for the purpose of reducing

test time (column 8, lines 47 – 51). A first linear automaton circuit, also known as a

Multiple-input Shift Register (MISR) with the function $z(t + 1) = Az(t)$ XOR $y(t)$ is a well

known design choice in the art, and the use of the well known design choice would yield

predictable results.

6.   Regarding claim 51, Hasegawa and Wu teach the limitations of the parent claim,

claim 35. Hasegawa additionally teaches: the first linear automaton circuit is designed

as a linear feedback, multi-input shift register or the second linear automaton circuit is

designed as a linear feedback, multi-input shift register. (figure 4, element 16, element

2)

7.   Regarding claim 52, Hasegawa and Wu teach the limitations of the parent claim,

claim 52. Hasegawa additionally teaches: the multi- input shift registers have a primitive

feedback polynomial of maximum length (paragraph 0081).

8.   Regarding claim 55, Hasegawa and Wu teach the limitations of the parent claim,

claim 35. Hasegawa additionally teaches: the evaluation circuit is monolithically

integrated on an integrated circuit (abstract).

Claims 36, 37, 39, 41 – 45, and 48 – 50 are rejected under 35 U.S.C. 103(a) as being unpatentable over Hasegawa and Wu, in view of Meaney, U.S. Patent 6,055,660 (herein Meaney).

9.   Regarding claim 36, Hasegawa and Wu teach the limitations of the parent claim, claim 35. Hasegawa does not explicitly teach: the logic combination gates are present as exclusive-OR gates whose first inputs are respectively connected to the outputs of the associated linear automaton circuit and to whose second inputs good signatures can be applied.

Meaney teaches: the logic combination gates are present as exclusive-OR gates whose first inputs are respectively connected to the outputs of the associated linear automaton circuit and to whose second inputs good signatures can be applied. (figure 2, element 13, element 22)

A person of ordinary skill in the art, at the time of the invention, would find it obvious to combine the teachings of Hasegawa, a first and second logic combination gate, with the teaching of Meaney, a first and second logic combination gate as an XOR gate. The use of XOR logic gates for comparison is well known in the art (column 4, line 13, element 22) and the combination would yield a predictable result.

10.   Regarding claim 37, Hasegawa and Wu teach the limitations of the parent claim, claim 35. Hasegawa does not explicitly teach: arranged upstream of the first linear

automaton circuit is a first coder, that encodes the data word y(i) having the data word

length of k bits into an encoded data word ul(i), ul(i)=Cod1 having the word width of K1

bits, for i=l, ..., n, and where Cod1 represents the encoding function of the first coder.

Meaney teaches: arranged upstream of the first linear automaton circuit is a first

coder, that encodes the data word y(i) having the data word length of k bits into a coded

data word ul(i), ul(i)=Cod1 having the word width of K1 bits, for i=l, ..., n, and where

Cod1 represents the encoding function of the first coder (figure 2, element 21).

A person of ordinary skill in the art, at the time of the invention, would find it

obvious to combine the teachings of Hasegawa, an evaluation circuit, as cited above,

with the teaching of Meaney: a first coder upstream of the first linear automation circuit

for the purpose of detection of errors introduced independent of the design under test.

Data encoders are a well known technique in the art for detecting errors in data. One of

ordinary skill in the art, at the time of the invention, would have recognized the

application of the known technique would have yielded predicable results.

11.   Regarding claim 39, Hasegawa and Wu teach the limitations of the parent claim,

claim 37. Hasegawa does not explicitly teach: arranged upstream of the second linear

automaton circuit is a second coder, which encodes the data word y(i) having the data

word length of k bits into an encoded data word u2(i), u2(i)=Cod2(y(i)) having the word

width of K2 bits, for i=1, ..., n, and where Cod2 represents the encoding function of the

second coder.

Meaney teaches: arranged upstream of the second linear automaton circuit is a second coder (figure 2, element 21'), which encodes the data word $y(i)$ having the data word length of k bits into an encoded data word $u2(i)$, $u2(i)=Cod2(y(i))$ having the word width of K2 bits, for i=1, ..., n, and where Cod2 represents the encoding function of the second coder (figure 2, element 21').

A person of ordinary skill in the art, at the time of the invention, would find it obvious to combine the teachings of Hasegawa, an evaluation circuit, as cited above, with the teaching of Meaney: a second coder upstream of the second linear automation circuit for the purpose of detection of errors introduced independent of the design under test. Data encoders are a well known technique in the art for detecting errors in data. One of ordinary skill in the art, at the time of the invention, would have recognized the application of the known technique would have yielded predicable results.

12.   Regarding claim 41, Hasegawa and Wu teach the limitations of the parent claim, claim 39. Hasegawa does not explicitly teach: the word width K1 of the data words $u1(i)$ encoded by the first coder is equal to the word width K2 of the data words $u2(i)$ encoded by the second coder.

Meaney teaches: the word width K1 of the data words $u1(i)$ encoded by the first coder is equal to the word width K2 of the data words $u2(i)$ encoded by the second coder (figure 2, element 23, element 23').

A person of ordinary skill in the art, at the time of the invention, would find it obvious to combine the teachings of Hasegawa, an evaluation circuit, as cited above,

with the teaching of Meaney: the first coder and second coder having the same data

output width for the purpose of providing symmetric data protection for the first and

second path. It is a well known design technique to replicate logic units to minimize

design and test of logic elements. One of ordinary skill in the art at the time of the

invention would recognize that applying the known technique would yield predictable

results.

13.   Regarding claim 42, Hasegawa and Wu teach the limitations of the parent claim,

claim 39. Hasegawa does not explicitly teach: the first coder matching the second

coder with regard to its construction and its function.

        Meaney teaches: the first coder matching the second coder with regard to its

construction and its function (figure 2, element 23, element 23')

        A person of ordinary skill in the art, at the time of the invention, would find it

obvious to combine the teachings of Hasegawa, an evaluation circuit, as cited above,

with the teaching of Meaney: the first coder and second coder having the same

construction and function. It is a well known design technique to replicate logic units to

minimize design and test of logic elements. One of ordinary skill in the art at the time of

the invention would recognize that applying the known technique would yield predictable

results.

14.   Regarding claim 43, Hasegawa and Wu teach the limitations of the parent claim,

claim 39. Hasegawa does not explicitly teach: the word width K1 of the data words $u^1(i)$

encoded by the first coder and the word width K2 of the data words $u^2(i)$ encoded by the

second coder are in each case equal to the word width k of the data words y(1), ..., y(n)

of the data stream Tn.

Meaney teaches: the word width K1 of the data words $u^1(i)$ encoded by the first

coder and the word width K2 of the data words $u^2(i)$ encoded by the second coder are in

each case equal to the word width k of the data words y(1), ..., y(n) of the data stream

Tn. (figure 2, element 25, element 22, element 23, element 25', element 22', element

23')

A person of ordinary skill in the art, at the time of the invention, would find it

obvious to combine the teachings of Hasegawa, an evaluation circuit, as cited above,

with the teaching of Meaney: the first coder and second coder having the same data

width of $u^1(i)$ and $u^2(i)$ as y(i). It is a well known design technique to replicate logic units

to minimize design and test of logic elements. One of ordinary skill in the art at the time

of the invention would recognize that applying the known technique would yield

predictable results.

15.   Regarding claim 44, Hasegawa and Wu teach the limitations of the parent claim,

claim 39. Hasegawa does not explicitly teach: the encoding functions Cod1 and Cod2

of the first coder and of the second coder are designed as follows:

$Cod1(y_1(i), y_2(i), ..., y_k(i)) = Pl(y_l(i), y_2(i), ..., y_k(i), 0, ..., 0)$

$Cod2(y_l(i), y_2(i), ..., y_k(i)) = P2(y_l(i), y_2(i), ..., y_k(i), 0, ..., 0)$

For i, 1, ..., n where the number of zeros situated at the end of P1($y_l(i)$, $y_2(i)$, ..., $y_k(i)$, 0, ..., 0) is equal to (K1-k), where the number at the end of P2($y_l(i)$, $y_2(i)$, ..., $y_k(i)$, 0, ..., 0) is equal to (K2-k), and where P 1 represents an arbitrary permutation of the K1 components of ($y_1(i)$, $y_2(i)$, ..., $y_k(i)$, 0, ...,0) and P2 represents an arbitrary permutation of the K2 components of ($y_1(i)$, $y_2(i)$, ..., $y_k(i)$, 0, ...,0) (figure 2, element 23, element 24, element 23', element 24').

Meaney teaches: the encoding functions Cod1 and Cod2 of the first coder and of the second coder are designed as follows:

Cod1($y_1(i)$, $y_2(i)$, ..., $y_k(i)$) = Pl($y_l(i)$, $y_2(i)$, ..., $y_k(i)$, 0, ..., 0)

Cod2($y_l(i)$, $y_2(i)$, ..., $y_k(i)$) = P2($y_l(i)$, $y_2(i)$, ..., $y_k(i)$, 0, ..., 0)

For i, 1, ..., n where the number of zeros situated at the end of P1($y_l(i)$, $y_2(i)$, ..., $y_k(i)$, 0, ..., 0) is equal to (K1-k), where the number at the end of P2($y_l(i)$, $y_2(i)$, ..., $y_k(i)$, 0, ..., 0) is equal to (K2-k), and where P 1 represents an arbitrary permutation of the K1 components of ($y_1(i)$, $y_2(i)$, ..., $y_k(i)$, 0, ...,0) and P2 represents an arbitrary permutation of the K2 components of ($y_1(i)$, $y_2(i)$, ..., $y_k(i)$, 0, ...,0) (figure 2, element 23, element 24, element 23', element 24').

A person of ordinary skill in the art, at the time of the invention, would find it obvious to combine the teachings of Hasegawa and Wu, an evaluation circuit, as cited above, with the teaching of Meaney, zero padding of code words. Zero padding of code words in a known technique in the art, and the combination would yield predictable results.

16.　　Regarding claim 45, Hasegawa and Wu teach the limitations of the parent claim, claim 37. Hasegawa does not explicitly teach: the coding functions Cod1 and Cod2 of the first coder and of the second coder are designed as follows:

$$Cod1(y_1(i), y_2(i), ..., y_k(i)) = P1(y_1(i), y_2(i), ..., y_k(i), b_1^1..., b_{K1}^1{}_k)$$

$$Cod2(y_l(i), y_2(i), ..., y_k(i)) = P2(y_l(i), y_2(i), ..., y_k(i), b_1^2..., b_{K1}^2{}_K)$$

and where P1 and P2 represent arbitrary permutations.

Meaney teaches: the coding functions Cod1 and Cod2 of the first coder and of the second coder are designed as follows:

$$Cod1(y_1(i), y_2(i), ..., y_k(i)) = P1(y_1(i), y_2(i), ..., y_k(i), b_1^1..., b_{K1}^1{}_k)$$

$$Cod2(y_l(i), y_2(i), ..., y_k(i)) = P2(y_l(i), y_2(i), ..., y_k(i), b_1^2..., b_{K1}^2{}_K)$$

and where P1 and P2 represent arbitrary permutations (figure 2, element 23, element 24, element 23', element 24').

A person of ordinary skill in the art, at the time of the invention, would find it obvious to combine the teachings of Hasegawa and Wu, an evaluation circuit, as cited above, with the teaching of Meaney, padding of code words with $b_1^n..., b_{K1}^n{}_k$. Padding of code words in a known technique in the art, and the combination would yield predictable results.

17.　　Regarding claim 48, Hasegawa and Wu teach the limitations of the parent claim, claim 35. Hasegawa does not explicitly teach: the state matrix A of the first linear automaton circuit and the state matrix B of the second linear automaton circuit are related to one another as follows: $B = A^n$ where $n \neq 1$.

Meaney teaches: the state matrix A of the first linear automaton circuit and the

state matrix B of the second linear automaton circuit are related to one another as

follows: $B = A^n$ where $n \neq 1$ (table 2)

A person of ordinary skill in the art, at the time of the invention, would find it

obvious to combine the teachings of Hasegawa and Wu, an evaluation circuit, as cited

above, with the teaching of Meaney, matrix $B = A^n$ where $n \neq 1$. Inverted matrices are a

well known design choice in MISR design is well known in the art, and combination

would yield predictable results.

18.   Regarding claim 49, Hasegawa and Wu teach the limitations of the parent claim,

claim 35. Hasegawa does not explicitly teach: the state matrix B of the second linear

automaton circuit is equal to the inverted state matrix A^{-1} of the first linear automaton

circuit.

Meaney teaches: the state matrix B of the second linear automaton circuit is

equal to the inverted state matrix A^{-1} of the first linear automaton circuit (table 2).

A person of ordinary skill in the art, at the time of the invention, would find it

obvious to combine the teachings of Hasegawa and Wu, an evaluation circuit, as cited

above, with the teaching of Meaney, matrix $B = A^{-1}$. Inverted matrices are a well known

design choice in MISR design is well known in the art, and combination would yield

predictable results.

19.   Regarding claim 50, Hasegawa and Wu teach the limitations of the parent claim, claim 35. Hasegawa does not explicitly teach: the first linear automaton circuit is designed as a linear feedback shift register and the second linear automaton circuit is designed as an inverse linear feedback shift register, both linear automaton circuits having a parallel input.

Meaney teaches: the first linear automaton circuit is designed as a linear feedback shift register and the second linear automaton circuit is designed as an inverse linear feedback shift register, both linear automaton circuits having a parallel input (table 2).

A person of ordinary skill in the art, at the time of the invention, would find it obvious to combine the teachings of Hasegawa and Wu, an evaluation circuit, as cited above, with the teaching of Meaney, the linear automaton circuits as linear feedback shift registers. Implementation of a linear automaton circuit as a linear feedback shift register is a well known design choice in the art and the combination would yield a predictable result.

Claims 38, 40, 46, and 47 are rejected under 35 U.S.C. 103(a) as being unpatentable over Hasegawa, Wu, and Meaney, in view of Applicant Admitted Prior Art (herein AAPA).

20.   Regarding claim 38, Hasegawa, Wu, and Meaney teach the limitations of the

parent claim, claim 35. Hasegawa does not explicitly teach: the following holds true for

the encoding function of the first coder:

Codl $(y'(i))$ = ul(i) (D $f_1(e(i))$, or

Cod1 $(y'(i))$ = Cod1 $(y(i)$ XOR $e(i))$ = Cod1 $(y(i)$ XOR $f_1(e(i)))$

where a function f_1 by $f_1(0)$ = 0 exists for $y'(i)$ = $y(i)$ XOR $e(i)$, and where a function f_1^{-1}

where $f_1^{-1}(f_1(e))$ = e exists for all binary data words e having the word width k which may

occur as errors of a data word, where e denotes a faulty data word of the data stream

Tn,

AAPA teaches: the following holds true for the encoding function of the first

coder:

Codl $(y'(i))$ = ul(i) (D $f_1(e(i))$, or

Cod1 $(y'(i))$ = Cod1 $(y(i)$ XOR $e(i))$ = Cod1 $(y(i)$ XOR $f_1(e(i)))$

where a function f_1 by $f_1(0)$ = 0 exists for $y'(i)$ = $y(i)$ XOR $e(i)$, and where a

function f_1^{-1} where $f_1^{-1}(f_1(e))$ = e exists for all binary data words e having the word width

k which may occur as errors of a data word, where e denotes a faulty data word of the

data stream Tn (page 6, lines 14 – 18).

A person of ordinary skill in the art, at the time of the invention, would find it

obvious to combine the teachings of Hasegawa, Wu, and Meaney, an evaluation circuit,

with a first coder upstream of a first linear automation circuit, with the teaching of

AAPA:, as cited above. Linear block codes, as defined above, are well known

technique in the art for error detection correction. One of ordinary skill, at the time of

the invention, would have recognized that application of the known technique would

yield predictable results.

21.   Regarding claim 40, Hasegawa, Wu, and Meaney teach the limitations of the

parent claim, claim 39. Hasegawa does not explicitly teach: the following holds true for

the encoding function of the second coder:

Cod2(y'(i)) = u2(i) ~ f2(e(i)), or

Cod2(y'(i)) = Cod2(y(i) • e(i)) = Cod2(y(i)) • f2(e(i))

where a function f_2^{-1} where $f_2^{-1}(f_2(e)) = e$ exists for all binary data words e having

the word width k which may occur as errors of a data word, where e denotes a faulty

data word of the data stream Tn.

AAPA teaches: the following holds true for the encoding function of the second coder:

Cod2(y'(i)) = u2(i) ~ f2(e(i)), or

Cod2(y'(i)) = Cod2(y(i) • e(i)) = Cod2(y(i)) • f2(e(i))

where a function f_2^{-1} where $f_2^{-1}(f_2(e)) = e$ exists for all binary data words e having

the word width k which may occur as errors of a data word, where e denotes a faulty

data word of the data stream Tn (page 6, lines 14 – 18).

A person of ordinary skill in the art, at the time of the invention, would find it

obvious to combine the teachings of Hasegawa, Wu, and Meaney, an evaluation circuit,

with a first coder upstream of a first linear automation circuit, with the teaching of

AAPA:, as cited above. Linear block codes, as defined above, are well known

technique in the art for error detection correction. One of ordinary skill, at the time of

the invention, would have recognized that application of the known technique would

yield predictable results.

22.   Regarding claim 46, Hasegawa, Wu, and Meaney teach the limitations of the

parent claim, claim 37. Hasegawa does not explicitly teach: the encoding function Cod1

of the first coder is designed such that it realizes a linear block code, f1=Cod1.

        AAPA teaches: the encoding function Cod1 of the first coder is designed such

that it realizes a linear block code, f1=Cod1 (page 6, lines 14 – 18).

        A person of ordinary skill in the art, at the time of the invention, would find it

obvious to combine the teachings of Hasegawa, Wu, and Meaney, an evaluation circuit,

with a first coder upstream of a first linear automation circuit, with the teaching of

AAPA:, as cited above. Linear block codes, as defined above, are well known

technique in the art for error detection correction. One of ordinary skill, at the time of

the invention, would have recognized that application of the known technique would

yield predictable results.

23.   Regarding claim 47, Hasegawa, Wu, and Meaney teach the limitations of the

parent claim, claim 39. Hasegawa does not explicitly teach: the encoding function Cod2

of the second coder is designed such that it realizes a linear block code, f2=Cod2.

        AAPA teaches: the encoding function Cod2 of the second coder is designed such

that it realizes a linear block code, f2=Cod2 (page 6, lines 14 – 18).

A person of ordinary skill in the art, at the time of the invention, would find it obvious to combine the teachings of Hasegawa, Wu, and Meaney, an evaluation circuit, with a first coder upstream of a first linear automation circuit, with the teaching of AAPA:, as cited above. Linear block codes, as defined above, are well known technique in the art for error detection correction. One of ordinary skill, at the time of the invention, would have recognized that application of the known technique would yield predictable results.

24.   Claim 56 is rejected under 35 U.S.C. 103(a) as being unpatentable over Hasegawa and Wu, in view of Eldridge et al., U.S. Publication 2001/0052786 (herein Eldridge).

25.   Regarding claim 56, Hasegawa and Wu teach the limitations of the parent claim, claim 35. Hasegawa does not explicitly teach: A load board for receiving at least one needle card for testing integrated circuits or having at least one test socket for testing integrated circuits or for connecting a handler to a tester of integrated circuits, the load board having an evaluation circuit.

Eldridge teaches: A load board for receiving at least one needle card for testing integrated circuits (paragraph 0075).

A person of ordinary skill in the art, at the time of the invention, would find it obvious to combine the teachings of Hasegawa and Wu, an evaluation circuit, as cited above, with the teaching of Eldridge, a load board for receiving a needle card. A load

board from receiving a needle card is well known in the art and one of ordinary skill in

the art, at the time of invention, would recognize the combination would yield predictable

results.

Claim 57 is rejected under 35 U.S.C. 103(a) as being unpatentable over

Hasegawa and Wu, in view of Beer, U.S. Publication 2002/0153918 (herein Beer).

26.   Regarding claim 57, Hasegawa and Wu teach the limitations of the parent claim,

claim 35. Hasegawa does not explicitly teach: a needle card for testing integrated

circuits.

Beer teaches: a needle card for testing integrated circuits (abstract).

A person of ordinary skill in the art, at the time of the invention, would find it

obvious to combine the teachings of Hasegawa and Wu, an evaluation circuit, as cited

above, with the teaching of Beer, a needle card. A needle card is well known in the art

and one of ordinary skill in the art, at the time of invention, would recognize the

combination would yield predictable results.

Claim 58 is rejected under 35 U.S.C. 103(a) as being unpatentable over

Hasegawa, Wu, and Eldridge, in view of Davis et al., U.S. Patent 6,194,910 (herein

Davis).

27.   Regarding claim 58, Hasegawa and Wu teach the limitations of the parent claim,

claim 35. Hasegawa does not explicitly teach: a tester for testing integrated circuits

having the following features: the tester is provided with a plurality of instruments for

generating signals or data streams and with a plurality of measuring sensors, in

particular for currents and voltages; the tester has a load board which is provided for

receiving at least one needle card for testing integrated circuits and/or for connecting a

handler to a tester of integrated circuits and/or which is equipped with at least one test

socket for testing integrated circuits.

Eldridge teaches: the tester has a load board which is provided for receiving at

least one needle card for testing integrated circuits and/or for connecting a handler to a

tester of integrated circuits and/or which is equipped with at least one test socket for

testing integrated circuits (paragraph 0075).

A person of ordinary skill in the art, at the time of the invention, would find it

obvious to combine the teachings of Hasegawa and Wu, an evaluation circuit, as cited

above, with the teaching of Eldridge, a load board for receiving a needle card. A load

board from receiving a needle card is well known in the art and one of ordinary skill in

the art, at the time of invention, would recognize the combination would yield predictable

results.

Eldridge does not explicitly teach: the tester is provided with a plurality of

instruments for generating signals or data streams and with a plurality of measuring

sensors, in particular for currents and voltages.

Davis teaches: the tester is provided with a plurality of instruments for generating

signals or data streams and with a plurality of measuring sensors, in particular for

currents and voltages (abstract).

A person of ordinary skill in the art, at the time of the invention, would find it obvious to combine the teachings of Hasegawa and Wu, an evaluation circuit, as cited above, with the teaching of Davis, a tester for measurement of voltage and current. A tester for measurement of voltage and current is well known in the art and one of ordinary skill in the art, at the time of invention, would recognize the combination would yield predictable results.

Allowable Subject Matter (old)

28.   The following is a statement of reasons for the indication of allowable subject matter: The prior art of record fails to discloses or teach:

undergoing transition to the state $z^2(n+1)= S_2(L2, y(1) ...., y(i-1), y(i), y(i+l) .... , y(n))$ if no error can be detected in the case of the data words $u2(1), ..., u2(i-1), u2(i), u2(i), ..., u2(n)$,

undergoing transition to the state $z^2(n+1)= S_2(L2, y(1), ..., y(i-1), y(i), y'(i), y(i+l), ..., y(n))$ if an error is present at least in the case of the i-th position of the coded data words $u2(1) ..... u2(i-1), u2'(i), u2(i) .... , u2(n)$,

the signature of an error-free data stream Tn being designated by $S(L2, y(1), ..., y(i-l), y(i), y(i+l), ..., y(n))$ and the signature of a faulty data stream Tn being designated by $S(L2, y(l), ..., y(i-1), y'(i), ..., y(n))$,

determining the signature differences $\Delta S1$ and $\Delta S2$ by means of exclusive-OR logic combinations of the signatures S1 and S2 with ascertained good signatures, in each case according to the following specifications:

$\Delta S1 = S(L1, y(1), ..., y(i-1), y(i), y(i+I), ..., y(n))$

$XOR\ S(L1, y(1), ..., y(i-1), y'(i), y(i+I)..., y(n))$

$\Delta S2 = S(L2, y(1), ..., y(i-1), y(i), y(i+I), ..., y(n))$

$XOR\ S(L2, y(1), ..., y(i-1), y'(i), y(i-\sim I), ..., y(n))$

determining a unique solution for the position i of the faulty bit in the faulty data

word by solving the equation $f_1^{-1}(A^{i-n}\ \Delta S1) = f_2^{-1}(B^{i-n}\ \Delta S2)$

and if no unique solution results for $1 \le i \le n$, outputting a notification by means of

an output medium that two or more errors are present in the data stream T, under

consideration,

determining a unique solution for the counter e(i) of the faulty data word y'(i) in

the data stream Tn by solving the equation

$e(i) = f_1^{-1}(A^{i-n}\ \Delta S1)$

outputting the position i of the faulty bit in the faulty data word and also the error

e(i) of the faulty data word y'(i) in the data stream Tn by means of an output medium.

Conclusion

Any inquiry concerning this communication or earlier communications from the

examiner should be directed to DANIEL F. MCMAHON whose telephone number is

(571)270-3232. The examiner can normally be reached on M-Th 8am-5pm(EST).

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Kevin Ellis can be reached on (571) 272-4205. The fax phone number for

the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the

Patent Application Information Retrieval (PAIR) system. Status information for

published applications may be obtained from either Private PAIR or Public PAIR.

Status information for unpublished applications is available through Private PAIR only.

For more information about the PAIR system, see http://pair-direct.uspto.gov. Should

you have questions on access to the Private PAIR system, contact the Electronic

Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a

USPTO Customer Service Representative or access to the automated information

system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Dfm
06/10/10

/Kevin L Ellis/
Supervisory Patent Examiner, Art Unit 2117